

# Cold Water Gasoline Belt Drive

The CWC Series features a 1¼-inch roll cage, handle and lifting hook, making this pressure washer one of the most powerful on the market today.

To see more online, scan here or go to [www.mitm.com](http://www.mitm.com):



### Pump

- External bypass system allows more water into the system to protect from heat build-up
- Forged brass manifold
- Thermal and safety relief valves
- Water filter with clear sleeve for screen inspection (High capacity water filter on CWC-3008-4MGH)

### Frame

- Industrial frame design includes powder coated steel frame with 1¼-inch roll cage, handles and lifting hook
- Two-piece belt guard with ¼-turn release
- Locking tire brake
- Pneumatic tires

### Components

- Fuel tank is powder coated outside and aluminized steel inside to prevent rusting
- 13.0-gallon fuel tank capacity for 9.5 hour run time

### Unit Includes:

- 50-foot x ¾-inch high pressure hose with quick connects (CWC-5000 models have non-marking hose; CWC-6004 has black hose)
- 50-foot x ½-inch high pressure black hose with quick connects (CWC-3008-4MGH)
- Insulated trigger gun with safety lock-off



CWC-6004-4MGH

Limited Warranties:

**3 Year**  
Honda Engine

**7 Year**  
Pump



Intertek  
Certified  
to UL-1776

CWC-5004-4MAH  
CWC-5004-4MGH  
CWC-5005-4MGH

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	UNLOADER	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CWC-3008-4MGH	3000	8.0	688cc Honda OHV, electric start - battery included	General	3-0279	Preset pressure	0°, 15°, 25° & 40°	48in.	43x27.75x36in.	531 lb.	408 lb.
CWC-5004-4MAH	5000	4.0	688cc Honda OHV, electric start - battery included	AR	3-0213	Preset pressure	0°, 15°, 25° & 40°	48in.	43x27.75x36in.	521 lb.	398 lb.
CWC-5004-4MGH	5000	4.0	688cc Honda OHV, electric start - battery included	General	3-0261	Preset pressure	0°, 15°, 25° & 40°	48in.	43x27.75x36in.	521 lb.	398 lb.
CWC-5005-4MGH	5000	5.0	688cc Honda OHV, electric start - battery included	General	3-0262	Preset pressure	0°, 15°, 25° & 40°	48in.	43x27.75x36in.	531 lb.	408 lb.
CWC-6004-4MGH	6000	3.7	688cc Honda OHV, electric start - battery included	General	3-0261	Preset pressure	0°, 15°, 25° & 40°	48in.	43x27.75x36in.	531 lb.	408 lb.

### Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
851-0089	50-ft. x ½-in. high pressure hose	CWC-3008-4MGH	AW-3000-0035	Sand injector	CWC-5004 & CWC-6004 models
851-0317	50-ft. x ¾-in. non-marking hose	CWC-5004 & CWC-5005 models	AW-7500-0035	Rotating nozzle	CWC-5004 & CWC-6004 models
851-0362	50-ft. x ¾-in. high pressure hose	CWC-6004-4MGH			