

Lowe[®]

Equipment Attachments



LOWE[®] Auger Attachments

LOWE[®] has a worldwide reputation for productive, durable products that perform day after day, job after job.

With quality components, welding and overall design, **LOWE[®]** augers will impress you over any of the competition. Motors with exceptional efficiency and full-flow lubrication result in cooler operation, more durability and less sensitivity to oil contamination.

LOWE[®] augers are so well designed that only two hydraulic lines are required. No third case drain line is ever needed.

Remember, without a high performance, durable attachment your equipment is doing less than it should. You owe it to yourself to find out why **LOWE[®]** is the way to go.

Remember to check out our trenching and grapple attachments!



BP & A Series Drive Units

Classic Series Drive Units



Productive, Durable, Value[®]

Lowe
Equipment Attachments

18903 High Point Road | Viola, WI 54664
TOLL FREE 1.800.356.9180 | PHONE 608.538.4000 | FAX 608.538.3995
E-MAIL Lowe@Loweman.com | www.loweman.com



MADE IN USA



18903 High Point Road | Viola, WI 54664
TOLL FREE 1.800.356.9180 | PHONE 608.538.4000 | FAX 608.538.3995
E-MAIL Lowe@Loweman.com | www.loweman.com



MADE IN USA

LOWE® Auger Customer Uses

Fence Builders, Deck & Home Builders, Landscaping-Trees & Shrub Planting, Concrete Contractors-Foundations, Highway Departments-Signs, Pole Building Companies, Utility Companies and Municipalities, Farmers, Electrical Contractors, Solar & Wind Generation Installation, Fence Building, Post Holes, Playground Equipment, Decks, Foundations, Signs, Light Poles, Clothes Lines.

Model	Suggested Flow	Rec. Max Auger Size
500 Classic	5-15 GPM (19-57 Lpm)	15-inch (381 mm)
750 Classic	8-20 GPM (36-76 Lpm)	24-inch (610 mm)
1200 Classic	10-20 GPM (36-76 Lpm)	30-inch (762 mm)
1650 Classic	14-25 GPM (53-95 Lpm)	36-inch (914 mm)
2175 Classic	16-25 GPM (60-95 Lpm)	36-inch (914 mm)
BP-150	10-20 GPM (38-76 Lpm)	30-inch (762 mm)
BP-210	15-30 GPM (57-114 Lpm)	36-inch (914 mm)
BP-230	18-30 GPM (68-114 Lpm)	48-inch (1,219 mm)
A-275	15-42 GPM (57-159 Lpm)	36-inch (914 mm)
A-400	22-42 GPM (83-159 Lpm)	48-inch (1,219 mm)

Suggestions and recommendations are subjective, based upon limitations and decades of real-world experience.

Classic Series Auger Drive Units:

New durability and performance levels, all with the traditional **LOWE®** look.

Ultra reliable **LOWE®** hydraulic motors, solid unit structures, heat-treated alloy shafts and an even heavier duty reduction drive are standard.

Balanced alignment means it is easier to drill a vertical hole. The protected hose routing minimizes component damage.

Productive, even more durable and an incredible value.

New BP-Series Auger Drive Units:

LOWE® designed and manufactured gearboxes specifically for auger attachment use. Features include: increased gear strength, stronger shaft support and through hardened alloy drive shaft.

American castings, gears, motors and other components.

Safe and Easy Carry Position!

