



## Features

- Comes in sizes 36", 42", and 48"
- Rocker switch on 120V, Single Phase models
- SJT type 3 conductor, 12' long cord on 120V, Single Phase models / no cord on dual voltage models
- Aluminum, 4 paddle blade
- Spiral, wire front and rear guards
- Corrosion and dent proof high density polyethylene housing
- 10" wheels
- Swivel model rotates 360° in 12-1/2° increments and locks in place with a steel locking pin
- External junction boxes on dual voltage models allow units to be wired for either voltage without removing guards
- Hazardous location models have explosion proof motors, metal housings, and external junction boxes rated for Class I, Group D and Class II, Groups E, F, & G, UL Listed
- Meets OSHA standards
  1 year limited warranty

## Motor Specifications

• 1-Speed

- Ball bearing
- Permanently lubricated

## Standard Models

MOTOR LISTING	SIZE	MOTOR					STANDARD MODEL			SWIVEL MODEL		
		TYPE	НР	CFM	RPM	AMPS	UPC# 686334	MODEL	WT. (LBS.)	UPC# 686334	MODEL	WT. (LBS.)
C CLISTED US	36"	120 V 1 PH ODP	1/2	14,500	500	8.0	796477	PB 36-B	120	796507	PBS 36-B	145
	42"		3/4	18,200	430	11.0	796484	PB 42-B	135	796514	PBS 42-B	160
	48"		1	22,700	390	15.0	796491	PB 48-B	155	796521	PBS 48-B	180
C CLASTED US	36"	240/480 V 3 PH ODP	1/2	14,500	500	2.3 / 1.1	850865	PB 36-B-3	127	850926	PBS 36-B-3	152
	42"		3/4	18,200	430	3.3 / 1.5	850872	PB 42-B-3	143	850933	PBS 42-B-3	168
	48"		1	22,700	390	3.4 / 1.7	850889	PB 48-B-3	164	850940	PBS 48-B-3	189
(Î)	36"	120/240 V 1 PH EXP	1/2	14,500	500	7.8 / 3.9	850896	PB 36-B-HL	135	850957	PBS 36-B-HL	160
	42"		3/4	18,200	430	10.8 / 5.4	850902	PB 42-B-HL	150	850964	PBS 42-B-HL	175
	48"		1	22,700	390	13.2 / 6.6	850919	PB 48-B-HL	173	850971	PBS 48-B-HL	198

Note: Products listed in this section are custom built and subject to 100% cancellation/restocking charges. Note: Photograph is a representation of stocked models. Actual model may vary slightly in appearance.