Troughing-Slider

Conveyor

Models

The E-Z LIFT Troughing-Slider Conveyor is a medium duty conveyor designed to move loose and packaged materials at inclines up to 30 degrees. The conveyor's unique combination slider/roller bed makes it E-Z LIFTS's most versitile belt conveyor. Reversible, this conveyor can quickly move materials in and out!

Typical uses include:

Dirt, gravel, sand, aggregates, grain, powders, cement, coal, and sludges. Cartons, shingles, firewood, rolls, and more!



Features include:

- Heavy duty 2 ply rubber covered belt with 2" high cleats on 48" centers
- · Combination slider/roller bed
- 7/8" O.D. high strength steel tubing for 12' & 16' models, 1-1/4" O.D. on 21' through 36' models
- 15" frame height
- Approximate 140 FPM belt speed
- · Conveyor belt take-up adjustments
- · Self cleaning drive and idler belt pulleys
- Drive mounted at side of discharge end
- For electric motor-direct drive speed reducer
- For gas engine internal V-belt and roller chain reduction, and safety guards
- Fork pockets
- Operating, maintenance, and safety instructions

Accessories:

- Electric motor or gas engine
- Start/Stop switch for electric motor
- Hopper
- Dolly and hitch assembly
- Tail-light assembly
- Towable elevating carriage

• Options:

- Smooth belt
- Belt wiper
- Mini-cleated belt
- Forward/Stop/Reverse switch for electric motor
- Corrosion resistant PVC idler rollers



Belt –14" wide			
Model	Length	Approx. Wgt*	
68-14	12 ft.	250 lbs.	
70-14	16 ft.	300 lbs.	
71-14	21 ft.	350 lbs.	
73-14	26 ft.	400 lbs.	
75-14	31 ft.	445 lbs.	
77-14	36 ft.	515 lbs.	

CAPACITIES – at 30° incline		
Lbs./Cu. Ft.	Tons/Hr.	
30	22	
50	36	
75	54	

Model	Length	Approx. Wgt:
68-18	12 ft.	265 lbs.
70-18	16 ft.	320 lbs.
71-18	21 ft.	375 lbs.
73-18	26 ft.	430 lbs.
75-18	31 ft.	490 lbs.
77-18	36 ft.	570 lbs.
CAPACITIES – at 30° incline		

Belt-18" wide

CAPACITIES – at 30° incline		
Lbs./Cu. Ft.	Tons/Hr.	
30	27	
50	45	
75	67	

Belt –24" wide			
Model	Length	Approx. Wgt	
68-24	12 ft.	273 lbs.	
70-24	16 ft.	343 lbs.	
71-24	21 ft.	413 lbs.	
73-24	26 ft.	475 lbs.	
75-24	31 ft.	565 lbs.	
77-24	36 ft.	670 lbs.	

CAPACITIES – at 30° incline		
Lbs./Cu. Ft.	Tons/Hr.	
30	36	
50	60	
75	90	
•		

Multilift, Inc.

2000 South Cherokee, Denver, Colorado 80223 Denver Area: 303.733.5533 FAX 303.733.5642 North American Toll Free: 1.800.821.9966

E-mail: ez@ezliftconveyors.com Website: www.ezliftconveyors.com